

Manopola standard, protezione frontale IP40 | Standard knob, IP40 front protection



Corrente nom. Nominal current AC-21A (A)	Posizioni Positions	Dimensioni Dimensions mm x mm	Unipolare 1 pole	Bipolare 2 poles	Tripolare 3 poles
			2 elementi / 2 elements	3 elementi / 3 elements	5 elementi / 5 elements
16	 45°	48 ●	CS16-57R-48S	—	—
25		54 ●	CS20-57R-54S	CS20-60R-54S	CS20-61R-54S
25		72 ●	CS20-57R-72S	CS20-60R-72S	CS20-61R-72S
25		72 ●	CS25-57R-72S	CS25-60R-72S	CS25-61R-72S
32		72 ●	CS32-57R-72S	—	—
			2 elementi / 2 elements	4 elementi / 4 elements	6 elementi / 6 elements
25	 45°	54 ●	CS20-58R-54S	CS20-62R-54S	CS20-63R-54S
25		72 ●	CS20-58R-72S	CS20-62R-72S	CS20-63R-72S
25		72 ●	CS25-58R-72S	CS25-62R-72S	CS25-63R-72S
32		72 ●	CS32-58R-72S	—	—
			3 elementi / 3 elements		
25	 45°	54 ●	CS20-59R-54S		
25		72 ●	CS20-59R-72S		
25		72 ●	CS25-59R-72S		
32		72 ●	CS32-59R-72S		
			3 elementi / 3 elements	6 elementi / 6 elements	9 elementi / 9 elements
25	 45°	54 ●	CS20-64R-54S	CS20-65R-54S	CS20-66R-54S
25		72 ●	CS20-64R-72S	CS20-65R-72S	CS20-66R-72S
			4 elementi / 4 elements		
16	 45°	48 ●	CS16-67R-48S		
20		54 ●	CS20-67R-54S		
20		72 ●	CS20-67R-72S		